

Amendments in the claims

Please amend the claims as set forth below.

Claims 1-22 (Canceled).

23. (Currently Amended) An air compressor unit comprising:

multiple compartments within the air compressor unit including at least first and second compartments,

an air compressor disposed in the first compartment and a motor disposed within the second compartment ~~the unit~~;

a rotary blower that draws air into the unit and generates an air flow through the unit;

an air intake port ~~permitting a single initial air flow to entering~~ the unit;

a discharge aperture ~~permitting a single final air flow to exiting~~ the unit;

~~multiple compartments within the unit through which an air flow passes, wherein~~
the multiple compartments are configured ~~arranged in parallel~~, such that a single initial air flow enters the unit through the intake port, the multiple compartments divide the initial air flow into at least first and second distinct multiple intermediate air flows with the first intermediate air flow flowing through the first compartment and the second intermediate air flow flowing through the second compartment, the ~~multiple~~ distinct intermediate air flows converge to ~~the~~ a single final air flow, ~~and the single final air flow that~~ exits the unit through the discharge aperture ~~compartment~~.

24. (Currently Amended) The unit of claim 23, wherein the multiple compartments include an intake compartment, a the first compartment, a the second compartment, and a discharge compartment.

25. (Currently Amended) The unit of claim 24, wherein the air intake port is in fluid flow communication with the intake compartment, and the initial air flow enters the intake compartment through the air intake port.

26. (Currently Amended) The unit of claim 24, wherein ~~the multiple intermediate air flows include a first air flow and a second air flow:~~

the first intermediate air flow passes through the first compartment and the discharge compartment;

the second intermediate air flow passes through the first compartment, the second compartment, and the discharge compartment; and

the first intermediate air flow and the second intermediate air flow converge into the final air flow in the discharge compartment.

27. (Original) The unit of claim 24, wherein the discharge aperture is in fluid flow communication with the discharge compartment, and the final air flow exits the discharge compartment through the discharge aperture.

Claims 28-29 (Canceled).

30. (Currently Amended) ~~The~~ An air compressor unit of claim 24, comprising:

multiple compartments within the air compressor unit including at least first and second compartments and a discharge compartment,

an air compressor and a motor disposed within the air compressor unit;

a rotary blower that draws air into the unit and generates an air flow through the unit;

an air intake port entering the unit; and

a discharge aperture exiting the unit;

wherein the multiple compartments are configured such that a single initial air flow enters the unit through the intake port, the multiple compartments divide the initial air flow into at least first and second distinct intermediate air flows with the first intermediate air flow flowing through the first compartment and the second intermediate air flow flowing through the second compartment, the distinct intermediate air flows converge to a single final air flow in the discharge compartment and exits the unit through the discharge aperture and wherein an aftercooler is disposed between the first compartment and the discharge compartment.

31. (Original) The unit of claim 24, wherein the rotary blower is disposed in the intake compartment.

32. (Currently Amended) ~~The~~ An air compressor unit of claim 24, comprising:

multiple compartments within the air compressor unit including at least first and second compartments and a discharge compartment,

an air compressor and a motor disposed within the air compressor unit;

a rotary blower that draws air into the unit and generates an air flow through the
unit;
an air intake port entering the unit; and
a discharge aperture exiting the unit;
wherein the multiple compartments are configured such that a single initial air
flow enters the unit through the intake port, the multiple compartments divide the initial air flow
into at least first and second distinct intermediate air flows with the first intermediate air flow
flowing through the first compartment and the second intermediate air flow flowing through the
second compartment, the distinct intermediate air flows converge to a single final air flow in the
discharge compartment and exits the unit through the discharge aperture and wherein a partition
at least partially separates the first compartment from the second compartment, and the partition
at least partially separates the second compartment from the discharge compartment.

33. (Original) The unit of claim 32, wherein the partition includes a layer of noise
absorbing foam.

34. (Original) The unit of claim 23, wherein the compressor is a reciprocating
compressor.

35. (Previously Presented) An air compressor unit comprising:
an intake compartment having an air intake permitting air to enter the air
compressor unit;

a blower disposed within the intake compartment drawing air into the intake compartment through the air intake, and generating an air flow through the unit;

a primary inlet permitting fluid flow between the intake compartment and a first compartment;

a secondary inlet permitting fluid flow between the intake compartment and a second compartment;

a first passage permitting fluid flow between the first compartment and a discharge compartment;

a second passage permitting fluid flow between the first compartment and a second compartment;

a third passage permitting fluid flow between the second compartment and the discharge compartment; and

a discharge aperture in fluid flow communication with the discharge aperture, permitting air to exit the unit.

36. (Original) The unit of claim 35, further comprising a compressor disposed within the first compartment.

37. (Original) The unit of claim 36, wherein the compressor is a reciprocating compressor.

38. (Original) The unit of claim 35, further comprising a motor disposed within the second compartment.

39. (Original) The unit of claim 35, further comprising an aftercooler disposed near the first passage.

B1 40. (Original) The unit of claim 35, wherein a partition at least partially separates the first compartment from the second compartment, and the partition at least partially separates the second compartment from the discharge compartment.

41. (Original) The unit of claim 40, wherein the partition includes a layer of noise absorbing foam.
